

XMT 350 MPa

Part No: MILXMT350MPACE

AUTO-LINE™ POWER MANAGEMENT

Automatically compensates for various input Voltage. Suits jobsite and generator power. Keeps welding output constant even if input power varies by ±10%. Single or 3 phase.

DINSE STYLE WELD DISCONNECTS

Provides high-quality weld cable connections.

FAN-ON-DEMAND™

The cooling system operates only when needed, reducing noise, energy use and the amount of contaminants pulled through machine.

LIFT-ARC™

Allows TIG starting without the use of high-frequency. Starts the arc without contaminating the weld with tungsten.

WIND TUNNEL TECHNOLOGY™

Protects electrical components and PC boards from contamination.

COMPATIBLE WITH INSIGHT CORE™

Simple internet-based welding information solution.

VRD TO CAT C AS 1674.2

INVERTER ARC CONTROL TECHNOLOGY

Provides greater puddle control for superior 6010 Stick electrode performance, and outstanding MIG weld performance.

ADAPTIVE HOT START™

Increases the output Amperage at the start of a weld if necessary, eliminating electrode sticking.

LIGHTWEIGHT, AEROSPACE-GRADE ALUMINIUM CASE

Offers heavy-duty protection with the benefit of reduced weight.

PROCESS SELECTOR SWITCH

Reduces the number of control setup combinations without reducing any features.

LARGE, DUAL DIGITAL METERS

Easy to view and can be pre-set.

3 YEAR WARRANTY

For details, refer to Miller's True Blue warranty statement.

BUILT-IN PULSED MIG PROGRAMS WITH SYNERGIC CAPABILITY

APPLICATIONS	PROCESSES
Construction	MIG (GMAW)
Shipbuilding	Pulsed MIG (GMAW-P)
Railroad	Stick (SMAW)
Truck/Trailer Manufacturing	TIG (GTAW)
Fabrication	Flux Cored (FCAW)
Repair Shops	Air Carbon Arc Cutting and Gouging (CAC-A)
Rental Fleets	
Power Generation Plants	



INPUT POWER	RATED OUTPUT	VOLTAGE RANGE - CV MODE	AMPERAGE RANGE IN CC MODE	INPUT AT RATED LOAD OUTPUT, 50/60HZ			DIM. (MM)	WEIGHT
				400 V 3P	kVA	kW		
3 Phase	350 A at 34 VDC, 60% Duty Cycle	10 - 38 V	15 - 425 A	20.6	14.2	13.6	H: 432 W: 318 D: 610	36.3kg